

MYPRIMER100

As a primer based on acrylic copolymers, used as a bonding bridge for absorbent surfaces before applying MyRevest microcement.



- Improves adhesion between absorbent substrates such as plasterboard or plaster and microcement.
- Easy to apply, ready-to-use product.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.

Technical Data

Properties	Specification	Unit	Method
Nature	Acrylic emulsion		
рН	7-8		UNE-EN ISO 19396- 1:2020
Density	1,02±0,05	g/cm3	UNE-EN ISO 2811-1
Non-volatile content	10-12	%	UNE-EN ISO 3251:2020
Performance	8-12	m2/L	
VOC:2024/42/IIA(h) (30)Max.VOCs	<5	g/L	
Drying time to the touch	30	minutes	

Application

The substrates must be clean and free of grease, oils, oxides, paint residues and loose or poorly adhered parts. Apply to the surface by brush or roller.

Cover the entire surface, taking care to apply a uniform film. The application temperature should be between 5-30° C. Wait approximately 1 hour before applying the microcement.

The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

latest edition: January 2025



Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the product safety data sheet. Empty containers must be disposed of in accordance with current legislation.

Presentation

It is available in 1 and 5 L containers.

Cleaning of tools

The tools are washed with water immediately after use.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.



