



**MYREVEST**  
PURE ELEGANCE

## MYSEALANTPOOL

**MySealant Pool** is a water-based lithium salt sealant for the **MyPool** system, which creates a protective and consolidating film.



### Properties

- It offers high durability and improved chemical and wear resistance.
- Resistant to the alkalinity of microcement.
- High adhesion.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.
- Easy application.

### Presentation

It comes in 5-litre containers.

### Technical information

Properties	Specification	Unit	Method
<b>Features</b>	Aqueous solution of Li salts		
<b>Non-volatile content</b>	14-16	%	UNE-EN ISO 3251:2020
<b>Density</b>	1,02±0,05	g/cm <sup>3</sup>	UNE-EN ISO 2811-1
<b>pH</b>	10.5-11.5		UNE-EN ISO 19396-1
<b>Drying time to touch (23°C RH:50%)</b>	30-60	min	
<b>Drying time between coats</b>	24	hours	
<b>Performance</b>	10-15	m <sup>2</sup> /L	

CHEMICAL RESISTANCES: Immersion method UNE-EN 13529

#### Legend

- 5: No visible change.
- 4: Slight change, only visible with change of light.
- 3: Moderate visible mark.
- 2: Significant marking without affecting surface structure.
- 1: Important mark, affects the surface structure.

The results obtained are based on an application of 2 coats of varnish 24 hours between coats and after 7 days of application. The contact with the chemical agent tested was 24 hours, one week and one month.



C/ Cuenca 21-4-8,  
46960 Valencia  
(Spain)

T.617955352  
info@myrevest.com  
www.myrevest.com

Product	Contact time 24 H	Contact time 1 week	Contact time 1 month
Water	5	5	5
Chlorinated water	5	5	5

## Application

Before application, be sure to thoroughly clean the surface. At least 24 hours should elapse before applying the sealer to the microcement. Shake MySealant Pool and apply by spraying at low pressure and spreading evenly by roller or brush to completely cover the substrate, avoiding areas of overspray. Allow each coat to dry for at least 24 hours before applying the next coat. Do not overcoat as this may cause incorrect curing and discolouration.

Avoid leaving traces. Allow to dry, do not add product before it is dry/consolidated. Wait at least 7 days after application of MySealant Pool before filling the pool.

The ambient temperature should be between 5 - 30°C, without excessive wind. The substrate temperature should be between 5 - 25°C.

## Storage

It should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.

## Special precautions

MySealant Pool is alkaline and may cause eye and skin irritation. Avoid prolonged contact with skin and eyes and wear appropriate protective equipment during application. See product data sheet.

## Cleaning of tools

Tools are washed with water, immediately after use.

The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

last edition: April 2025

