

MYJOINTER

MyJointer is a grout for manual application indoors and outdoors. The product is suitable for grouting tile joints in kitchens and bathrooms.



Properties

- High adhesion on a wide variety of substrates; tiles, ceramics, plaster, plasterboard, concrete, bricks, stone, mortar, painted surfaces, etc.
- Good resistance to water and ambient humidity.
- Retains flexibility after drying.
- Easy to apply and sand.

Limitations

- Do not apply at temperatures below 10°C and above 35°C and humidity above 80%.
- Do not apply on substrates subject to permanent humidity.
- Do not apply on heated surfaces or in direct sunlight.
- Do not apply on substrates subject to permanent humidity. This product is not suitable for coating surfaces that are to be painted afterwards.

Technical information

Properties	Specification	Unit	Method
Features	Acrylic Putty		
Colour	White cream		
Non-volatile content	83-85	%	UNE-EN ISO 3251:2020
Density	1,6±0,1	g/cm ³	UNE-EN ISO 2811-1
Thickness of application	<4	mm	
COV:2004/42/A(c)(40)MaxCOVs	<1	g/L	
Drying time to touch (23°C RH:50%)	5-6	hours	
Complete drying time	12-24	hours	
Performance applied on joints of tile	0,24	kg/m ² /mm	

Substrate preparation and application

- Before applying **MyJointer**, it is essential to check that the substrate is stable and completely clean.
- Stir contents before use. Application material: spatula or trowel. Maximum application thickness up to 4 mm per coat.
- Depending on the environmental conditions and the ventilation of the working space, it is necessary to allow 12-24 hours to elapse before applying the microcement.

Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the safety data sheet of the product.

Empty containers must be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use.

Cleaning of tools

The tools are washed with water immediately after use.

Storage conditions

The product must be stored in its original closed and unopened packaging sheltered from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.

Presentation

It is available in 1.5 and 6 kg packages.

The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements. The Safety Data Sheets of the product are available to the professional.

last edition: March 2025



**trademark
of quality
for professionals**